



**NOTES:**

1. SPECIFICATION: MIL-PRF-26542F
2. SLASH SHEET: MIL-PRF-26542/10
3. SENSITIVITY: 56dB MIN./ 103 dB INPUT
4. TYPE: DYNAMIC
5. IMPEDANCE: 150 OHM +/- 15%
6. FREQUENCY RESPONSE: 300 Hz - 6.0kHz
7. WATER PROOF
8. COLOR: BLACK
9. MATES: U-173/U CONNECTOR

**PROPRIETARY AND CONFIDENTIAL**  
 THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF <INSERT COMPANY NAME HERE>. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF <INSERT COMPANY NAME HERE> IS PROHIBITED.

		UNLESS OTHERWISE SPECIFIED:		NAME	DATE	<b>LIVE WIRE</b> TITLE: MICROPHONE DYNAMIC M-138/G SIZE DWG. NO. REV <b>B</b> M-138_G-LW SCALE: 2:1 WEIGHT: SHEET 1 OF 1		
		DIMENSIONS ARE IN INCHES		DRAWN	MC			12/3/20
		TOLERANCES: +/- .010		CHECKED				
		FRACTIONAL ±		ENG APPR.				
		ANGULAR: MACH ± BEND ±		MFG APPR.				
		TWO PLACE DECIMAL ±		Q.A.				
		THREE PLACE DECIMAL ±		COMMENTS:				
		INTERPRET GEOMETRIC TOLERANCING PER:						
		MATERIAL						
		FINISH						
NEXT ASSY	USED ON	APPLICATION		DO NOT SCALE DRAWING				