



- NOTES:
 MICROPHONE:
 1. SPECIFICATION: MIL-PRF-26542F
 2. SLASH SHEET: MIL-PRF-26542/8C
 3. SENSITIVITY: 56dB MIN./ 103 dB INPUT
 4. TYPE: DYNAMIC
 5. IMPEDANCE: 150 OHM +/- 15%
 6. FREQUENCY RESPONSE: 300 Hz - 6.0kHz
 7. WATER PROOF
 8. COLOR: BLACK

PROPRIETARY AND CONFIDENTIAL
 THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF HERBERT COMPANY NAME HERE. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF HERBERT COMPANY NAME HERE IS PROHIBITED.

UNLESS OTHERWISE SPECIFIED:		NAME	DATE	LIVE WIRE
DIMENSIONS ARE IN INCHES TOLERANCES: FRACTIONAL \pm $-.010$ DECIMAL \pm $-.005$ ANGULAR: MATCH \pm BEND \pm TWO PLACE DECIMAL \pm THREE PLACE DECIMAL \pm		MC	12/3/20	
INTERPRET GEOMETRIC TOLERANCING PER: MATERIAL:		CHECKED		SIZE DWG. NO. REV
NEXT ASSY USED ON FINISH		ENG APPR.		C MC-ECVC-8011HO-001
APPLICATION DO NOT SCALE DRAWING		MFG APPR.		SCALE: 2:1 WEIGHT: SHEET 1 OF 1
		Q.A.		
		COMMENTS:		